

dinkey CC

The simplest version of Dinkey LED spotlight.
Fed with constant current.

Dinkey CC is installed with standardized connectors cables and accessories. Beam angles is controlled with interchangeable lenses. Mounting on LED square profiles.

Routing of separate cables makes it possible to control individual fixtures via external dimmable drivers.



TECHNICAL SPECIFICATION

Material	Lamp housing of die-cast magnesium
Finish	Grey (RAL 9006) Black (RAL 9005) White (RAL 9016)
System	LED profile High/Low Surface mounting
Operating power	Max. 1200 mA
Color temperature	2700K
CRI	90+
Protection class	IP20
Swivels	>360°
Tilts	>90°
Beam angle	8° 12° 22° 30° Elliptical
Dimming	Dimmable via driver

Dinkey CC

Comes with adapter for snap-in mounting on LED profile High/Low.



<input type="checkbox"/>	DIN42-1	Max 1200 mA, 12°, 2700K, adapter
<input checked="" type="checkbox"/>	DIN42-2	Max 1200 mA, 12°, 2700K, adapter
<input type="checkbox"/>	DIN42-3	Max 1200 mA, 12°, 2700K, adapter

Dinkey CC Yoke

For solitaire and custom installation. Comes with 8mm tube and nuts for easy installation.



<input checked="" type="checkbox"/>	DIN41-1	Max 1200 mA, 12°, 2700K, 1m connector cable
<input checked="" type="checkbox"/>	DIN41-2	Max 1200 mA, 12°, 2700K, 1m connector cable
<input type="checkbox"/>	DIN41-3	Max 1200 mA, 12°, 2700K, 1m connector cable

