

gizmo

Gizmo is designed to discreetly illuminate objects in museum cabinets and alike.

It is small and easy to integrate. It has a color neutral warm light evenly distributed over the spectrum. Close to incandescent light.







TECHNICAL SPECIFICATION

Material	Machined aluminium
Finish	Grey (RAL 9006) Black (RAL 9005) White Brass
System	LED profile High/Low Pico Trac Surface mounting
Operating power	350–700 mA
Light effect	1,2–2,4W
Color temperature	2700K
CRI	90+
Protection class	IP20
Swivels	>360°
Tilts	>90°
Beam angle	8° 10° 20° 35° 9x48°

Gizmo yoke

Gizmo yoke for surface mounting and custom installation. Comes with 8mm tube and nuts for easy installation.






	GIZ27-B-1	2700K, 350–700 mA, 10°, 1m connector cable
	GIZ27-B-2	2700K, 350–700 mA, 10°, 1m connector cable
	GIZ27-B-3	2700K, 350–700 mA, 10°, 1m connector cable
	GIZ27-B-M	2700K, 350–700 mA, 10°, machined brass

Gizmo adapter

Gizmo with adapter for mounting on LED square profiles.






	GIZ27-AF-1	2700K, 350–700 mA, 10°, adapter
	GIZ27-AF-2	2700K, 350–700 mA, 10°, adapter
	GIZ27-AF-3	2700K, 350–700 mA, 10°, adapter

Gizmo PT

Gizmo for mounting on Pico Trac low voltage track.



	GIZ27-PT-1	2700K, 10°, with dimmer
	GIZ27-PT-1	2700K, 10°, with dimmer
	GIZ27-PT-1	2700K, 10°, with dimmer



gizmo Zoom



Gizmo zoom is provided with a movable PC lense of high quality.

Variable light beam 5–31°.



TECHNICAL SPECIFICATION

Material	Machined aluminium
Finish	Grey (RAL 9006) Black (RAL 9005) White
System	LED profile High/Low Pico Trac Surface mounting
Operating power	350–700 mA
Light effect	1,2–2,4W
CRI	90+
Color temperature	2700K
Protection class	IP20
Swivels	>360°
Tilts	>90°
Beam angle	Adjustable 5–31°



Gizmo Zoom yoke

Gizmo Zoom yoke for surface mounting and custom installation.



- GIZz27-B-1 2700K, 350–700 mA, 5–31°, 1m connecting cable
- GIZz27-B-2 2700K, 350–700 mA, 5–31°, 1m connecting cable
- GIZz27-B-3 2700K, 350–700 mA, 5–31°, 1m connecting cable

Gizmo Zoom adapter

Gizmo Zoom with adapter for mounting on LED square profiles.



- GIZz27-AF-1 2700K, 350–700 mA, 5–31°, adapter
- GIZz27-AF-2 2700K, 350–700 mA, 5–31°, adapter
- GIZz27-AF-3 2700K, 350–700 mA, 5–31°, adapter

Gizmo Zoom PT

Gizmo Zoom for mounting on Pico Trac low voltage track.



- GIZz27-PT-1 2700K, 5–31°, with dimmer
- GIZz27-PT-2 2700K, 5–31°, with dimmer
- GIZz27-PT-3 2700K, 5–31°, with dimmer

